



PROGEF Standard installation fitting type 312 metric

Model:

- Material: PP-H
- Threaded outlet 1 1/4" NPSM
- Top saddle with EPDM gasket
- Stainless steel bolts and nuts

Range of use:

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512
- suitable for all plastic pipes

Attention:

- sensor length depends on installation fitting
- working temperature max. +40°C (water)

d	DN	PN	Code	Weight	L	L1	H	H1	D	Insertion Sensor Length
(mm)	(mm)	(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	
75	65	8	727 312 072	0.488	78	62	172	88	34	X1 (DN125 - DN200, 5" to 8")
90	80	8	727 312 073	0.514	86	69	186	87	34	X1 (DN125 - DN200, 5" to 8")
110	100	8	727 312 074	0.602	98	79	206	86	34	X1 (DN125 - DN200, 5" to 8")
125	100	8	727 312 075	0.667	101	85	212	78	34	X1 (DN125 - DN200, 5" to 8")
140	125	6	727 312 076	0.949	114	104	227	75	34	X1 (DN125 - DN200, 5" to 8")
160	150	6	727 312 077	0.985	114	114	243	72	34	X1 (DN125 - DN200, 5" to 8")
180	150	6	727 312 078	2.118	168	134	348	144	34	X2 (DN250 - DN900, 10" to 36")
200	200	6	727 312 079	2.045	168	132	357	142	34	X2 (DN250 - DN900, 10" to 36")
225	200	5	727 312 080	2.211	174	146	375	136	34	X2 (DN250 - DN900, 10" to 36")
250	250	5	727 312 081	2.616	179	159	397	131	34	X2 (DN250 - DN900, 10" to 36")
280	250	5	727 312 082	3.583	179	167	426	127	34	X2 (DN250 - DN900, 10" to 36")
315	300	5	727 312 083	4.311	248	202	450	120	34	X2 (DN250 - DN900, 10" to 36")

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>