


**ELGEF Plus Transition elbow 90° PE/brass
d25-63mm / SDR11 / Loose nut G**



- **PE 100 SDR 11** (ISO S5)
- 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit
- Incl. flat gasket for water applications (KTW / WRAS approved)

d (mm)	Thread Type	Size (inch)	DN (mm)	PN (bar)	Code	Weight (kg)	Do (mm)	L1 (mm)	Suitable for
25	Rp	¾	20	16	720 100 007	0.240	36	90	Pipe SDR 9-11
32	Rp	1	25	16	720 100 008	0.347	44	91	Pipe SDR 9-11
50	Rp	1 ½	40	16	720 100 010	0.850	66	116	Pipe SDR 9-11
63	Rp	1	50	16	720 100 021	1.114	81	121	Pipe SDR 9-17.6
63	Rp	2	50	16	720 100 011	1.375	81	129	Pipe SDR 9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>