


PROGEF Standard Diaphragm valve type 605 With butt fusion spigot metric

Model:

- Material: PP-H
- Compact full plastic design without screws
- High flow rate
- Actuator housing with thread for easy maintenance
- Quick opening & closing times
- For easy installation and removal
- Market standard installation length

Option:

- Individual configuration of the valve

* O-Ring material: FKM

d (mm)	DN (mm)	Size (inch)	PN (bar)	kv-value ($\Delta p=1$ bar) (l/min)	Actuator	EPDM Code	FKM Code	Weight (kg)
20	15	½	6	125	FC	167 605 112	167 605 162	0.31
20	15	½	6	125	FO	167 605 114	167 605 164	0.28
20	15	½	6	125	DA	167 605 115	167 605 165	0.26

d (mm)	PTFE/ EPDM* Code
20	167 605 132
20	167 605 134
20	167 605 135

d	D	D1_G	H	H1	H2	H3	H4	H7	L	L2	e	M	z	Lift = Hx
(mm)	(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
20	65	¼	89	14	12	46	30	42	124	25	1.9	M6	100	6
20	65	¼	89	14	12	46	30	42	124	25	1.9	M6	100	6
20	65	¼	89	14	12	46	30	42	124	25	1.9	M6	100	6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>