Data sheet

valid from: 4/5/26



95
Union elbow, flat seat, ISO/EN UA1

Supplied without sealing gaskets; a and z2 include the seal thickness as per table "Sealing Gasket Dimension".
374 G ... refers to the thread size G according to ISO 228 of the union nut 374.
* Inside hexagon

	Dim. (inch)	Thread size	Black Code	Galvanised Code	SP	GP
EN *	⅜	3/4	**770 095 103**	**770 095 203**	40	
EN *	½	1	**770 095 104**	**770 095 204**	10	
EN *	¾	1 1/4	**770 095 105**	**770 095 205**	10	
EN *	1	1 1/2	**770 095 106**	**770 095 206**	25	
EN *	1 ¼	2	**770 095 107**	**770 095 207**	12	
EN *	1 ½	2 1/4	**770 095 108**	**770 095 208**	10	
EN *	2	2 3/4	**770 095 109**	**770 095 209**	5	

	Dim. (inch)	Thread size	a (mm)	c (mm)	z1 (mm)	z2 (mm)	s1 (mm)	s2 (mm)
EN *	⅜	3/4	52	25	15	42	12	32
EN *	½	1	58	28	15	45	26	41
EN *	¾	1 1/4	62	33	18	47	31	48
EN *	1	1 1/2	72	38	21	55	38	55
EN *	1 ¼	2	82	45	26	63	48	67
EN *	1 ½	2 1/4	90	50	31	71	54	74
EN *	2	2 3/4	100	58	34	76	67	90

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com