



Tees



ELGEF Plus Tee 90° PE100 d20-63mm / SDR11 / with integral pipe fixation

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators

d	DN	PN	SDR	Code	Weight	d1	L	L1	z	z1	H	SDR pipe
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
20	15	16	11	753 211 606	0.085	35	88	32	11	92	67	9-11
25	20	16	11	753 211 607	0.075	35	90	32	11	92	70	9-11
32	25	16	11	753 211 608	0.118	44	102	34	15	100	74	9-11
40	32	16	11	753 211 609	0.175	54	119	39	21	114	82	9-11
50	40	16	11	753 211 610	0.252	66	135	42	24	126	90	9-11
63	50	16	11	753 211 611	0.407	81	151	46	28	150	102	9-17.6



ELGEF Plus Tee 90° PE100 d75-180mm / SDR11

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators




d	DN	PN	SDR	Code	Weight	d1	L	L1	z	z1	H	SDR pipe
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
75	65	16	11	753 211 612	0.569	97	178	54	35	143	87	9-17.6
90	80	16	11	753 201 813	0.891	115	205	62	41	161	94	9-17.6
110	100	16	11	753 201 814	1.576	140	255	72	56	184	104	9-17.6
125	100	16	11	753 201 815	2.212	161	276	78	60	207	113	9-17.6
140	125	16	11	753 201 816	3.639	185	300	83	67	260	120	9-17.6
160	150	16	11	753 201 817	4.386	196	325	92	71	206	103	11-17.6
180	150	16	11	753 201 818	6.796	225	344	90	82	250	110	11-17.6



ELGEF Plus Tee 90° PE100 d200-250mm / SDR11

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- Two separate fusion zones



d	DN	PN	SDR	Code	Weight	d1	L	L1	z	z1	H	SDR pipe
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
200	200	16	11	753 201 819	10.800	250	590	104	191	250	117	11-26
225	200	16	11	753 201 820	15.900	280	636	112	206	270	122	11-26
250	250	16	11	753 201 821	18.900	310	685	123	220	288	127	11-26