



ELGEF Plus Branch saddle topload PE100
d450-1000mm / SDR11 / Outlet d315 mm

- 10 bar Gas / 16 bar Water
- Branch saddle installation only with installation set Topload TL500 (799.300.809)
- Angle adaptors (799.350.340) for fusion cable required
- 4 mm pin connectors
- Spigot outlet for butt- and electrofusion
- Full pressure applicable - no derating factor
- With integrated thread for pressure test with separate pressure test cap 799.199.288 (outlet d315) / 799.199.289 (outlet d500)



d	d2	Do1	DN	PN	Code	Weight
(mm)	(mm)	(mm)	(mm)	(bar)		(kg)
450	232	315	450	16	193 135 436	18.500
500	232	315	500	16	193 135 446	17.000
560	232	315	600	16	193 135 456	16.100
630	232	315	600	16	193 135 466	15.950
710	232	315	700	16	193 135 476	14.800
800	232	315	800	16	193 135 486	14.300
900	232	315	900	16	193 135 496	13.800
1000	232	315	1000	16	193 135 506	13.500

d	Lmax	Q1	W	H	Hmax	Suitable for
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	
450	500	174	500	216	346	SDR Pipe 11-26
500	500	174	500	216	337	SDR Pipe 11-26
560	500	174	500	216	327	SDR Pipe 11-26
630	500	174	500	216	312	SDR Pipe 11-33
710	500	174	500	216	297	SDR Pipe 11-33
800	500	174	500	216	287	SDR Pipe 11-33
900	500	174	500	216	281	SDR Pipe 11-33
1000	500	174	500	216	274	SDR Pipe 11-33

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>