



Data sheet

valid from: 5/5/25



Barrel nipple ABS metric

Model:

- For the shortest possible distance between fittings
- Overall length L = 2 x socket length
- With solvent cement spigots on both sides

d (mm)	Size (inch)	PN (bar)	Code	Weight (kg)	L (mm)	closest inch (inch)
20		16	729 900 906	0.008	32	1/2
25		16	729 900 907	0.008	38	3/4
32		10	729 900 908	0.007	44	1
40		10	729 900 909	0.016	52	1 1/4
50		10	729 900 910	0.032	62	1 1/2
63		10	729 900 911	0.059	76	2
75	2 1/2	10	729 900 912	0.095	88	2 1/2
90		10	729 900 913	0.161	102	3
110		10	729 900 914	0.282	122	4
	3/8	10	729 901 905	0.002	28	
	1/2	10	729 901 906	0.004	32	
	3/4	10	729 901 907	0.008	38	
	1	10	729 901 908	0.015	44	
	1 1/4	10	729 901 909	0.027	52	
	1 1/2	10	729 901 910	0.050	62	
	2	10	729 901 911	0.098	76	
	3	10	729 901 913	0.266	102	
	4	10	729 901 914	0.476	122	

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>