


PVC Branch 45° and 67° SN4 (KGEA)



Material	PVC-U
Ring stiffness	SN4 (also used with SN2 pipes)
Colour	Orange (RAL 8023)
Application	Non-pressure underground sewage and rainwater drainage outside buildings
Joining	Socket with EPDM sealing ring
Temperature	Max. 60 °C for D 110–200; 40 °C for D 250–500 (60 °C short-term)

Code	D/D1 (mm)	α (°)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L (mm)
FVE0019	110/110	45	25	134	134	275
FVE0134	125/110	45	18	144	141	290
FVE0075	125/125	45	28	152	152	310
FVE0020	160/110	45	2	168	159	318
FVE0095	160/125	45	13	176	170	340
FVE0043	160/160	45	36	194	194	387
FVE0021	200/110	45	-14	197	182	358
FVE0135	200/125	45	-3	205	192	379
FVE0081	200/160	45	21	223	216	426
FVE0023	200/200	45	48	243	243	485
FVE0125	250/110	45	41	228	209	484
FVE0185	250/125	45	30	236	220	484
FVE0025	250/160	45	6	254	244	484
FVE0156	250/200	45	33	275	271	537
FVE0072	250/250	45	66	304	304	604
FVE0140	315/110	45	-9	272	244	491
FVE0158	315/125	45	-19	279	254	491
FVE0103	315/160	45	-43	297	278	491

Code	D/D1 (mm)	α (°)	Z1 (mm)	Z2 (mm)	Z3 (mm)	L (mm)
FVE0154	315/200	45	7	318	305	568
FVE0174	315/250	45	40	345	338	633
FVE0141	315/315	45	84	382	382	722
FVE0257	400/125	45	-94	400	400	740
FPI0207	400/160	45	-77	358	327	545
FVE0236	400/200	45	-49	379	354	598
FVI0052	400/250	45	35	445	440	820
FVE0254	400/315	45	73	530	480	883
FVI0040	400/400	45	170	535	510	1020
FVE0289	500/160	45	-65	680	450	965
FVI0207	500/200	45	87	575	400	937
FVI0110	500/250	45	-10	530	510	970
FVI0111	500/315	45	-45	503	475	970
FVE0314	500/400	45	115	640	615	1180
FVE0315	500/500	45	240	675	665	1355
FVE0091	110/110	67	39	80	86	240
FVE0173	160/160	67	48	115	120	385

Dimensions as published by the manufacturer; symbols refer to the drawing above.