





**SYGEF Standard Diaphragm valve DIASTAR Ten
DA (Double acting)
With ECTFE butt fusion spigots (IR) metric**

Model:

- Diaphragm valve material: **PVDF** / end connection material: **ECTFE**
- SDR21/PN10
- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Rotating air connection at 90° intervals
- For easy installation and removal
- Short overall length

Option:

- Individual configuration of the valve
- Comprehensive range of accessories available

Working Pressure: **one side**

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	PTFE/ EPDM* Code	Weight (kg)
20	15	10	125	185 654 232	0.565
25	20	10	271	185 654 233	1.116
32	25	10	481	185 654 234	1.328
40	32	10	759	185 654 235	2.116
50	40	10	1263	185 654 236	3.426
63	50	10	1728	185 654 237	4.518

d (mm)	D (mm)	D1_G (inch)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	H5 (mm)	H7 (mm)	L (mm)	L2 (mm)	M	z (mm)	Lift = Hx (mm)
20	68	1/8	101	14	12	60	24	16	43	196	25	M6	100	7
25	96	1/8	132	18	12	73	25	16	57	221	25	M6	118	10
32	96	1/8	143	22	12	84	25	16	57	234	25	M6	126	13
40	120	1/8	173	26	15	99	26	26	69	260	45	M8	144	15
50	150	1/4	214	32	15	119	36	26	88	284	45	M8	164	19
63	150	1/4	226	39	15	132	36	26	88	321	45	M8	194	23

d (mm)	closest inch (inch)
20	1/2
25	3/4
32	1
40	1 1/4
50	1 1/2
63	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>