




ecoFIT outlet flange adaptor PE100
d40-315mm / SDR17/17.6

Model:

- Conventional butt-welding according to DVS 2207
- Suitable for wafer check valves Type 369

Attention:

- In conjunction with Outlet flange adaptors, **flange rings for socket systems** must be used.



d	Di	DN	SDR	PN	Code	Weight	Lmax	D1	Q2	s2	r	b1	BD
(mm)	(mm)	(mm)		(bar)		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
40	37	32	17	10	733 808 009	0.060	64	80	30	2.3	3	11	50
50	43	40	17	10	733 808 010	0.067	67	90	30	2.9	3	12	61
63	54	50	17	10	733 808 011	0.159	74	105	30	3.6	4	14	76
75	70	65	17	10	733 808 012	0.219	78	125	30	4.3	4	16	90
90	82	80	17	10	733 808 013	0.314	87	140	35	5.1	4	17	108
110	105	100	17	10	733 808 014	0.465	102	160	41	6.3	4	18	131
140	130	125	17	10	733 808 016	0.862	124	190	47	8.0	4	18	165
160	158	150	17	10	733 808 017	1.176	149	215	52	9.1	4	18	188
225	206	200	17	10	733 808 020	2.484	180	270	55	12.8	4	24	248
280	259	250	17	10	733 808 022	2.230	240	325	63	15.9	4	25	308
315	308	300	17	10	733 808 023	2.450	272	375	66	17.9	4	25	346

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>