




Data sheet

valid from: 2/7/25



ABS Ball valve type 127 24V With manual emergency override With threaded sockets ABS ISO Rp

Model:

- IP68 Rating
- Factory set control range 90°<)
- Heating element, position feedback (Open/Close)
- Integrated stainless steel mounting inserts

Option:

- Other valve and actuator configurations available
- Optional accessories: Fail-safe return unit

d	DN	Size	Thread Type	PN	kv-value	EPDM	Weight
(mm)	(mm)	(inch)		(bar)	($\Delta p=1$ bar)	Code	(kg)
					(l/min)		
16	10	3/8	Rp	10	70	199 127 692	2.100
20	15	1/2	Rp	10	185	199 127 693	2.100
25	20	3/4	Rp	10	350	199 127 694	2.200
32	25	1	Rp	10	700	199 127 695	2.300
40	32	1 1/4	Rp	10	1000	199 127 696	2.600
50	40	1 1/2	Rp	10	1600	199 127 697	3.000
63	50	2	Rp	10	3100	199 127 698	3.800

d	Actuator	B3	DE1	E	G	H	H1	H4	L	L1	Lz	M1	M2	M	z
(mm)		(mm)	(mm)	(mm)	(inch)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	EA15	25	50	122	M6	197	27	12	95	33	28	77	83	161	69
20	EA15	25	50	122	M6	197	27	12	100	33	28	77	83	161	67
25	EA15	25	58	122	M6	201	30	12	114	33	33	77	83	161	78
32	EA15	25	68	122	M6	207	36	12	127	33	36	77	83	161	85
40	EA15	45	84	122	M8	213	44	15	146	33	43	77	83	161	100
50	EA15	45	97	122	M8	219	51	15	152	33	45	77	83	161	106
63	EA15	45	124	122	M8	234	64	15	177	33	51	77	83	161	121

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>