

**Diaphragm valve DIASTAR TenPlus PVC-C
FC (Fail safe to close)
Unions with solvent cement sockets metric**

Model:

- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Rotating air connection at 90° intervals
- For easy installation and removal
- Short overall length


Option:

- Individual configuration of the valve
- Comprehensive range of accessories available

* PN: PTFE

Working Pressure: **both sides**

* O-Ring material: FKM



d (mm)	DN (mm)	Size (inch)	PN (bar)	PN* (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	SP	Weight (kg)
20	15	½	10	10*	125	163 684 012	1	1.004
25	20	¾	10	10*	271	163 684 013	1	1.142
32	25	1	10	10*	481	163 684 014	1	1.968
40	32	1 ¼	10	10*	759	163 684 015	1	3.375
50	40	1 ½	10	10*	1263	163 684 016	1	5.340
63	50	2	10	10*	1728	163 684 017	1	6.300

d (mm)	PTFE/ EPDM* Code	SP	Weight (kg)
20	163 684 032	1	1.012
25	163 684 033	1	1.153
32	163 684 034	1	1.987
40	163 684 035	1	3.395
50	163 684 036	1	5.368
63	163 684 037	1	6.327

d (mm)	D (mm)	D1_G (inch)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	H5 (mm)	H7 (mm)	L (mm)	L2 (mm)	M	z (mm)	Lift = Hx (mm)
20	96	¾	127	14	12	68	25	16	57	128	25	M6	96	7
25	96	¾	132	18	12	73	25	16	57	152	25	M6	114	10
32	120	½	167	22	12	93	26	26	69	166	25	M6	122	13
40	150	¾	196	26	15	101	36	26	88	192	45	M8	140	15
50	180	¾	239	32	15	124	37	26	103	222	45	M8	160	19
63	180	¾	251	39	15	137	37	26	103	266	45	M8	190	23

d (mm)	closest inch (inch)
20	¾
25	¾
32	1
40	1 ¼
50	1 ½
63	2

Data sheet

valid from: 4/6/26



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>