



SYGEF Standard Lug-style end installation butterfly valve type 578
With hand lever
Flange standard metric

Model:




- Housing material: PP-GF30 with SS316 lug-inserts
- Overall length according to EN 558, ISO 5752 (DN50 - 200 line 25, DN250 - 300 line 10)
- Connecting dimension: ISO 7005 PN10, EN 1092 PN10, DIN 2501 PN10
- We recommend for the dimensions DN250 and DN300 only 6 bar maximum system pressure for the hand lever version

Option:

- Optional accessory: Valve-Integrated position feedback with limit switches (limit switches have to be ordered separately)

Note:

For some material combination (e.g. DN300 valves with PE/PP pipes) special flange adapters are needed. Please check the "Perfect flange connection tool" on www.gfps.com



d	Size	DN	PN	kv-value	FKM	Weight	PTFE
(mm)	(inch)	(mm)	(bar)	($\Delta p=1$ bar)	Code	(kg)	Code
				(l/min)			
63	2	50	10	740	175 578 002	1.800	175 578 202
75	2 1/2	65	10	1500	175 578 003	1.895	175 578 203
90	3	80	10	2400	175 578 004	2.251	175 578 204
110	4	100	10	3800	175 578 005	3.146	175 578 205
140	5	125	10	8600	175 578 006	4.660	175 578 206
160	6	150	10	11400	175 578 007	6.430	175 578 207
225	8	200	10	19900	175 578 008	8.625	175 578 208
280	10	250	6	34000	175 578 009	19.528	175 578 209
315	12	300	6	50000	175 578 010	26.106	175 578 210

d	Hmax	Lmax	Wmax	U	V	H4	V1	Lg	D2	Q1	Q2	d2	k	Y
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	278.9	115.2	287.8	90	133.3	23	78.8	44.7	160	40		M16	125	66.8
75	291.8	115.2	296.3	90	139.9	23	85.1	45.7	180	54	35	M16	145	66.8
90	303.6	115.2	310.3	90	145.6	23	91.2	48.7	195	67	50	M16	160	66.8
110	343.6	115.2	375.2	90	166.0	23	107.5	55.6	226	88	74	M16	180	70.1
140	372.8	115.2	391.2	90	180.0	23	122.7	63.5	258	113	97	M16	210	70.1
160	393.6	115.2	395.2	90	189.0	23	134.5	71.5	284	139	123	M20	240	70.1
225	458.1	149.4	588.4	90	210.5	23	161.5	72.5	341	178	169	M20	295	86.1
280	557.6	149.4	628.1	125	264.4	23	206.9	113.2	412	210	207	M20	350	86.3
315	607.0	149.4	663.1	125	285.2	23	235.5	114.6	482	256	253	M20	400	86.3

d	M1	M2
(mm)	(mm)	(mm)
63	63.7	205.3
75	63.7	205.3
90	63.7	205.3
110	63.7	255.2
140	63.7	255.2
160	63.7	255.2
225	101.7	408.4
280	101.7	408.1
315	101.7	408.1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 9/25/26



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>