



ecoFIT Adaptor union PE80
d20-63mm / brass / Male thread R

Model:

- Union End: Fusion socket, metric
- Brass resistant to dezincification for use in drinking water applications
- Union Nut: brass
- Gasket: O-ring NBR (Nitrile-rubber)

d	Thread Type	Size	DN	SDR	PN	Code	Weight
(mm)		(inch)	(mm)		(bar)		(kg)
20	R	½	15	11	10	733 580 706	0.260
25	R	¾	20	11	10	733 580 707	0.324
32	R	1	25	11	10	733 580 708	0.470
40	R	1 ¼	32	11	10	733 580 709	0.754
50	R	1 ½	40	11	10	733 580 710	0.781
63	R	2	50	11	10	733 580 711	1.166

d	O-Ring	O-Ring NBR	Do	Lmax	G	z1	z2
(mm)			(mm)	(mm)	(inch)	(mm)	(mm)
20	3.53x23.39mm	745410001	46	62	1 1/4	6	40
25	3.53x28.17mm	745410007	52	65	1 1/2	6	41
32	3.53x36.10mm	745410002	64	71	2	6	45
40	5.34x43.82mm	745410003	79	78	2 1/2	8	48
50	5.34x53.34mm	745410012	85	81	2 3/4	8	43
63	5.33x69.22mm	745410013	104	91	3 1/2	8	54

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>