



GF 800 - 1000 - 1200

Butt fusion machine for construction site

Butt Fusion machine to joint PE, PP pipes and fittings for pressure piping systems on building sites and in trenches.

Hydraulically operated with manual control unit.

Control box with integrated temperature controller and power outlets.

For proper handling of the heating element and planer we recommend the assembling of the hoist unit (to be ordered separately).

Including transport packaging (wooden crate); reduction clamping inserts and other accessories to be ordered separately.

• BASE MACHINE

- High precision design, distortion-free and sturdy machine frame
- Good accessibility thanks to 45° inclination
- The movable (sliding) 3rd clamp allows easy and time-saving fixation of bends or tees without need of additional tools
- Double-sided heating element pull-off mechanism to optimise the change-over phase
- Weight: Type 800 = 690 kg, Type 1000 = 1238 kg, Type 1200 = 1370 kg

• HYDRAULIC UNIT

- Compact and robust, with full closed metal housing and two handles for carrying
- Precise pressure setting and fine adjusting
- Joystick operation of machine carriage
- Clearly visible, vibration-free pressure gauge with precision scaling
- Accumulator for pressure equalization during the cooling phase
- Max operating pressure: 200 bar
- Weight: 41 kg

• PLANER

- Powerful parallel planer for single or double-sided facing of pipe ends
- Planer with Stop mechanism for safety
- Safety microswitch to prevent undesired start-up
- Weight: Type 800 = 185 kg, Type 1000 = 308 kg, Type 1200 = 356 kg

• HEATING ELEMENT

- High performance, electronically controlled heating element
- High-quality, non-stick PTFE-coating with long service life
- Temperature indicator integrated into the handle
- Input voltage: 400 V
- Weight: Type 800 = 56 kg, Type 1000 = 88 kg, Type 1200 = 101 kg
- Input power: Type 800 = 12 kW, Type 1000 = 15 kW, Type 1200 = 16 kW

• CONTROL BOX

- Contains all safety and functional components such as static relay, FI protective switch, temperature control
- Compact unit in steel box with enamel-coated protective frame
- Integrated power outlets for all machine components, only 1 plug to the generator
- Weight: 29 kg

• CASE

- For safe storage of planer and heating element
- Weight: Type 800 = 226 kg, Type 1000 = 341 kg, Type 1200 = 412 kg

Type	d-d (mm)	Performance	Code	Weight (kg)
GF 800	500 - 800	400 V/15000 W	790 123 025	1550.000
GF 1000	630 - 1000	400 V/19500 W	790 124 025	2443.000
GF 1200	710 - 1200	400 V/20500 W	790 125 025	2668.000

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 5/1/26



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>