



PROGEF Standard Check valve type 561
Without spring
With threaded sockets reinforced Rp

Model:

- Material: PP-H
- Sealing at a minimum water column of 2 m
- Designed for easy installation and removal
- Vibration free even at high flow velocity
- Flow-optimized return cone, double guided
- For vertical installation
- Compact installation length, same as ball valve type 546
- Z-length, end connectors and union nuts **not** compatible with type 360

d	DN	Thread Type	Size	PN	kv-value	EPDM	Weight	FKM	Weight
(mm)	(mm)		(inch)	(bar)	($\Delta p=1$ bar)	Code	(kg)	Code	(kg)
					(L/min)				
16	10	Rp	$\frac{3}{8}$	10	190	167 561 021	0.080	167 561 031	0.080
20	15	Rp	$\frac{1}{2}$	10	180	167 561 022	0.090	167 561 032	0.090
25	20	Rp	$\frac{3}{4}$	10	380	167 561 023	0.170	167 561 033	0.180
32	25	Rp	1	10	460	167 561 024	0.200	167 561 034	0.210
40	32	Rp	1 $\frac{1}{4}$	10	850	167 561 025	0.350	167 561 035	0.360
50	40	Rp	1 $\frac{1}{2}$	10	1080	167 561 026	0.500	167 561 036	0.510
63	50	Rp	2	10	1670	167 561 027	0.920	167 561 037	0.920

D	L	L2	z
(mm)	(mm)	(mm)	(mm)
50	96	56	69
50	99	56	67
58	111	65	78
68	127	71	85
84	146	85	100
97	157	89	106
124	183	101	121

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>