



ecoFIT 3-Way ball valve type 543 Pro ABS
Horizontal/L-port
With butt fusion spigots long PE100 SDR11 metric

Model:

- Lockable lever as standard (DN10-DN50)
- Material: ABS/PE
- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seat PTFE
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Delivery status A-C opened, see flow scheme
- Z-dimension, valve end and union nut are compatible with type 543 (1stGeneration)

Option:

- Interface-module with position feedback sensor, incl. LED feedback (DN10-50)
- Manual spring return lever ("Dead man") (DN10-25)
- Pneumatic or electric actuators from GF
- Individual configuration of the valve possible

d	DN	Size	PN	kv-value	EPDM	Weight
(mm)	(mm)	(inch)	(bar)	($\Delta p=1$ bar)	Code	(kg)
				(l/min)		
20	15	½	10	75	169 543 302	0.203
25	20	¾	10	150	169 543 303	0.296
32	25	1	10	280	169 543 304	0.450
40	32	1 ¼	10	480	169 543 305	0.762
50	40	1 ½	10	620	169 543 306	1.161
63	50	2	10	1230	169 543 307	2.509

d	DN	D	L	L1	L2	L3	L4	L5	L6	H	H1	H2	M	e	closest
(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	inch
															(inch)
20	15	50	210	82	73	36	25	35	47	61	28	8	6	1.9	½
25	20	58	237	106	86	43	25	44	62	74	32	8	6	2.3	¾
32	25	68	251	106	99	50	25	44	62	80	36	8	6	2.9	1
40	32	84	283	131	120	60	45	57	74	95	45	9	8	3.7	1 ¼
50	40	97	319	131	137	69	45	57	74	102	51	9	8	4.6	1 ½
63	50	124	399	152	179	89	45	66	86	117	65	9	8	5.8	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>