



Elbow 90° PVC-C metric Rp

Model:

- With solvent cement socket metric and parallel female thread Rp
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-C

Rp	d	PN	Code	SP	Weight	z1	z2	D	L
(inch)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
½	20	16	723 100 206	10	0.024	11	14	30	27
¾	25	16	723 100 207	10	0.037	14	17	35	33
1	32	16	723 100 208	10	0.063	17	22	45	39
1 ¼	40	16	723 100 209	10	0.134	23	27	55	50
1 ½	50	16	723 100 210	5	0.199	27	36	62	58
2	63	16	723 100 211	10	0.337	33	46	75	73

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>