



Multi/Clamp Saddle Studs threaded outlet 1"

Model:

- Saddle with threaded outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Outlet dimension up to 4" available on request
- Lower shell half is without gasket (available on request)
- Other sizes available on request
- Not suitable for the use on plastic pipes
- Water and gas: NBR according to EN 682 (-10°C up to +70°C); potable water: EPDM according to EN 681-1 (-10°C up to +55°C)
- For working pressures in GAS please consult Georg Fischer Waga N.V.

Range (mm)	max Pressure (bar)	NBR Code
68 - 78	16	724 201 063
88 - 110	16	724 201 075
108 - 134	16	724 201 099
133 - 155	16	724 201 135
159 - 181	16	724 201 171
168 - 190	16	724 201 195
190 - 212	16	724 201 207
216 - 238	16	724 201 219
238 - 260	16	724 201 243
267 - 289	16	724 201 255

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>