


ELGEF Plus Transition elbow 90° PE/brass
d20-63mm / SDR11 / Male thread R



- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit



d	Thread Type	Size	DN	PN	Code	Weight
(mm)		(inch)	(mm)	(bar)		(kg)
20	R	½	15	16	720 100 756	0.240
25	R	¾	20	16	720 100 757	0.260
32	R	1	25	16	720 100 758	0.368
32	R	1 ¼	25	16	720 100 766	0.500
32	R	1 ½	25	16	720 100 767	0.562
40	R	1	32	16	720 100 771	0.511
40	R	1 ¼	32	16	720 100 759	0.534
40	R	1 ½	32	16	720 100 772	0.615
50	R	1	40	16	720 100 776	0.677
50	R	1 ¼	40	16	720 100 777	0.771
50	R	1 ½	40	16	720 100 760	0.734
63	R	1 ¼	50	16	720 100 782	1.040
63	R	1 ½	50	16	720 100 783	1.039
63	R	2	50	16	720 100 761	1.108

d	Do	L1	P1	SLW	Suitable for
(mm)	(mm)	(mm)	(mm)	(mm)	
20	31	96	32	30	Pipe SDR 9-11
25	36	97	32	35	Pipe SDR 9-11
32	44	98	34	40	Pipe SDR 9-11
32	44	100	34	50	Pipe SDR 9-11
32	44	100	34	60	Pipe SDR 9-11
40	54	107	38	50	Pipe SDR 9-11
40	54	109	38	50	Pipe SDR 9-11
40	54	109	38	60	Pipe SDR 9-11
50	66	116	42	60	Pipe SDR 9-11
50	66	118	42	60	Pipe SDR 9-11
50	66	118	42	60	Pipe SDR 9-11
63	81	128	46	70	Pipe SDR 9-17.6
63	81	128	46	70	Pipe SDR 9-17.6
63	81	132	46	70	Pipe SDR 9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>