





**PROGEF Standard Diaphragm valve DIASTAR Ten
FO (Fail safe to open)
With socket fusion spigots metric**

Model:

- Material: PP-H
- Double flow rate compared to predecessor
- One housing nut replaces four screws
- Rotating air connection at 90° intervals
- Overall length EN 558

Option:

- Individual configuration of the valve
- Comprehensive range of accessories available

* PN: PTFE

Working Pressure: **one side**

* O-Ring material: FKM

d (mm)	DN (mm)	Size (inch)	PN (bar)	PN* (bar)	kv-value (Δp=1 bar) (l/min)	EPDM Code	Weight (kg)	PTFE/ EPDM* Code	Weight (kg)
20	15	½	10	10*	125	167 645 012	0.442	167 645 032	0.452
25	20	¾	10	10*	271	167 645 013	0.805	167 645 033	0.816
32	25	1	10	10*	481	167 645 014	0.956	167 645 034	0.976
40	32	1 ¼	10	10*	759	167 645 015	1.537	167 645 035	1.557
50	40	1 ½	10	10*	1263	167 645 016	3.255	167 645 036	3.285
63	50	2	10	10*	1728	167 645 017	3.812	167 645 037	3.840

d (mm)	D (mm)	D1_G (inch)	H (mm)	H1 (mm)	H2 (mm)	H3 (mm)	H4 (mm)	H5 (mm)	H7 (mm)	L (mm)	L2 (mm)	M (mm)	e (mm)	Lift = Hx (mm)
20	68	¾	101	14	12	60	24	16	43	124	25	M6	1.9	7
25	96	¾	132	18	12	73	25	16	57	144	25	M6	2.3	10
32	96	¾	143	22	12	84	25	16	57	154	25	M6	2.9	13
40	120	¾	173	26	15	99	26	26	69	174	45	M8	3.7	15
50	150	¾	214	32	15	119	36	26	88	194	45	M8	4.6	19
63	150	¾	226	39	15	132	36	26	88	224	45	M8	5.8	23

d (mm)	closest inch (inch)
20	¾
25	¾
32	1
40	1 ¼
50	1 ½
63	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>