



PROGEF Standard 3-Way ball valve type 543 Pro P

Horizontal/T-port

Without manual override

With socket fusion spigots metric

Model:

- Material: PP-H
- Actuator fails safe to the closed position FC
- Control pressure supply through integrated NAMUR interface according VDI/VDE 3845 with 5.6 bar (81.2 psi)
- Basic position B-C opened, activated position A-B-C opened, see flow scheme
- Control time $90^\circ \leq 1-2s$
- For easy installation and removal
- Integrated stainless steel mounting inserts
- Full plastic solution (actuator housing made of PP-GF)
- Visual position indicator
- Z-dimension, valve end and union nut are compatible with types 285 – 288 and 543 (1st Generation)

Option:

- Position feedback sensor, incl. LED feedback (DN10-50) - PNP, NPN and NAMUR
- Positioner RPC, RPC D, RPC PID
- Individual configuration of the valve

d	DN	Size	PN	kv-value	EPDM	SP	Weight	FKM	SP	Weight
(mm)	(mm)	(inch)	(bar)	(Δp=1 bar)	Code		(kg)	Code		(kg)
				(l/min)						
16	10	3/8	10	140	199 296 042	1	1.035	199 296 052	1	1.035
20	15	1/2	10	200	199 296 043	1	1.041	199 296 053	1	1.041
25	20	3/4	10	470	199 296 044	1	1.134	199 296 054	1	1.134
32	25	1	10	793	199 296 045	1	1.261	199 296 055	1	1.261
40	32	1 1/4	10	1290	199 296 046	1	2.224	199 296 056	1	2.224
50	40	1 1/2	10	1910	199 296 047	1	2.541	199 296 057	1	2.541
63	50	2	10	3100	199 296 048	1	3.473	199 296 058	1	3.473

d	Actuator	D	H	H1	H2	H3	H4	H5	H6	L	L1	L2	L3	L4	L6
(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	PPA08	50	157	28	62	95	41	75	8	126	159	72	36	25	74
20	PPA08	50	157	28	62	95	41	75	8	136	159	72	36	25	74
25	PPA15	58	179	32	71	108	45	88	8	159	211	85	43	25	94
32	PPA15	68	179	36	71	108	45	88	8	178	211	98	49	25	94
40	PPA40	84	215	45	84	131	56	111	9	204	246	118	59	45	120
50	PPA40	97	215	51	84	131	56	111	9	237	246	135	68	45	120
63	PPA40	124	237	65	106	131	56	111	9	296	246	176	88	45	120

d (mm)	L7 (mm)	M	closest inch (inch)
16	32	6	$\frac{3}{8}$
20	32	6	$\frac{1}{2}$
25	38	6	$\frac{3}{4}$
32	38	6	1
40	47	8	1 $\frac{1}{4}$
50	47	8	1 $\frac{1}{2}$
63	47	8	2

Data sheet

valid from: 8/27/26



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>