




ecoFIT Adaptor union PE80
d20-63mm / brass / Female thread Rp

Model:

- Union End: Fusion socket, metric
- Brass resistant to dezincification for use in drinking water applications
- Union Nut: brass
- Gasket: O-ring NBR (Nitrile-rubber)



d	Thread Type	Size	DN	SDR	PN	Code	Weight
(mm)		(inch)	(mm)		(bar)		(kg)
20	Rp	½	15	17	10	733 580 206	0.209
25	Rp	¾	20	17	10	733 580 207	0.269
32	Rp	1	25	17	10	733 580 208	0.376
40	Rp	1 ¼	32	17	10	733 580 209	0.596
50	Rp	1 ½	40	17	10	733 580 210	0.666
63	Rp	2		17	10	733 580 211	0.960

d	O-Ring	O-Ring NBR	Do	Lmax	G	z1	z2
(mm)			(mm)	(mm)	(inch)	(mm)	(mm)
20	3.53x23.39mm	745410001	46	46	1 1/4	9	9
25	3.53x28.17mm	745410007	52	48	1 1/2	10	9
32	3.53x36.10mm	745410002	64	51	2	10	9
40	5.34x43.82mm	745410003	79	56	2 1/2	13	9
50	5.34x53.34mm	745410012	85	59	2 3/4	13	9
63	5.33x69.22mm	745410013	104	65	3 1/2	14	9

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>