


## MULTI/JOINT® 3207 Plus Wide Range end cap blind, restraint, Uni/Fiksers



### Model:

- Suitable for all kinds of pipe material
- Suitable for water and gas
- Ductile cast iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information
- Hygiene protection included DN50 - DN600

DN (mm)	Range 1 (mm)	NBR / A2 Code	EPDM / A2 Code	Weight (kg)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
50	46 - 71	709 375 210	709 375 610	3.500	709 375 010	709 375 310	3.500
65	63 - 90	709 375 212	709 375 612	4.100	709 375 012	709 375 312	4.100
80	84 - 105	709 375 214	709 375 614	5.100	709 375 014	709 375 314	5.100
100	104 - 132	709 375 216	709 375 616	6.500	709 375 016	709 375 316	6.500
125	132 - 155	709 375 218	709 375 618	7.800	709 375 018	709 375 318	7.800
150	154 - 192	709 375 220	709 375 620	9.600	709 375 020	709 375 320	9.600
200	192 - 232	709 375 224	709 375 624	18.300	709 375 024	709 375 324	18.300
225	230 - 268	709 375 226	709 375 626	20.900	709 375 026	709 375 326	20.900
250	267 - 310	709 375 228	709 375 628	27.100	709 375 028	709 375 328	27.100
300	315 - 356	709 375 232	709 375 632	34.400	709 375 032	709 375 332	34.400
400	392 - 433	709 375 234	709 375 634	43.100	709 375 034	709 375 334	43.100

DN (mm)	a (mm)	b (mm)	d (mm)	e (mm)	PN Water (bar)	PN Gas (bar)
50	115 - 130	164	100	3xM12	16.0	8
65	145 - 157	186	95	3xM12	16.0	8
80	142 - 156	204	115	3xM12	16.0	8
100	144 - 163	236	110	3xM16	16.0	8
125	151 - 169	264	120	4xM16	16.0	8
150	149 - 177	304	120	4xM16	16.0	8
200	180 - 207	354	140	6xM16	16.0	8
225	211 - 242	386	145	6xM20	16.0	8
250	214 - 249	432	170	6xM20	16.0	8
300	219 - 254	490	170	8xM20	16.0	8
400	253 - 295	574	205	10xM20	10.0	5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>