



3-Way ball valve type 543 PVC-C
Horizontal/L-port
With solvent cement spigots metric

Model:

- For easy installation and removal (valve end and union nut are compatible with type 546)
- Ball seals PTFE
- Pneumatic or electric actuator available separately
- Angle of operation 360° without turn limiter
- Turn limiter 90° enclosed, in different positions usable as a clip-on ring
- Integrated stainless steel mounting inserts
- Delivery status A-C opened, see flow scheme

d (mm)	DN (mm)	PN (bar)	kv-value ($\Delta p=1$ bar) (L/min)	EPDM Code	SP	Weight (kg)	FPM Code	SP	Weight (kg)
16	10	10	50	163 543 021	1	0.272	163 543 031	1	0.272
20	15	10	75	163 543 022	1	0.282	163 543 032	1	0.282
25	20	10	150	163 543 023	1	0.408	163 543 033	1	0.408
32	25	10	280	163 543 024	1	0.624	163 543 034	1	0.624
40	32	10	480	163 543 025	1	1.041	163 543 035	1	1.041
50	40	10	620	163 543 026	1	1.578	163 543 036	1	1.578
63	50	10	1230	163 543 027	1	3.075	163 543 037	1	3.075

d (mm)	D (mm)	H (mm)	H1 (mm)	H2 (mm)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	L5 (mm)	L6 (mm)	L7 (mm)	M	closest inch (inch)
16	50	57	28	8	131	77	73	36	25	32	45	137	6	$\frac{3}{8}$
20	50	57	28	8	141	77	73	36	25	32	45	147	6	$\frac{1}{2}$
25	58	67	32	8	165	97	86	43	25	39	58	171	6	$\frac{3}{4}$
32	68	73	36	8	182	97	99	50	25	39	58	188	6	1
40	84	90	45	9	209	128	120	60	45	54	74	215	8	1 $\frac{1}{4}$
50	97	97	51	9	242	128	137	69	45	54	74	248	8	1 $\frac{1}{2}$
63	124	116	65	9	302	152	179	89	45	66	87	308	8	2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>