



**Variable area flow meter type 335**  
**Float in PVDF with magnet**  
**With solvent cement sockets PVC-U metric**

**Model:**

- Suitable limit switches see accessories for variable area flow meters

Scale range (L/h)	d (mm)	DN (mm)	Taper tube in PVC-U transp. O- Rings in EPDM Code	Weight (kg)	Taper tube in Polyamid O-rings in EPDM Code	Weight (kg)	Taper tube in Polysulfone O-rings in EPDM Code	Weight (kg)
50 - 500	32	25	<b>198 335 100</b>	0.469	<b>198 335 120</b>	0.434	<b>198 335 140</b>	0.466
100 - 1000	32	25	<b>198 335 101</b>	0.547	<b>198 335 121</b>	0.423	<b>198 335 141</b>	0.452
150 - 1500	40	32	<b>198 335 102</b>	0.630	<b>198 335 122</b>	0.568	<b>198 335 142</b>	0.604
250 - 2500	40	32	<b>198 335 103</b>	0.714	<b>198 335 123</b>	0.547	<b>198 335 143</b>	0.585
200 - 2000	50	40	<b>198 335 104</b>	0.973	<b>198 335 124</b>	0.887	<b>198 335 144</b>	0.944
300 - 3000	50	40	<b>198 335 105</b>	0.952	<b>198 335 125</b>	0.874	<b>198 335 145</b>	1.035
600 - 6000	50	40	<b>198 335 106</b>	1.024	<b>198 335 126</b>	0.836	<b>198 335 146</b>	0.881
600 - 6000	63	50	<b>198 335 107</b>	1.342	<b>198 335 127</b>	1.240	<b>198 335 147</b>	1.360
1000 - 10000	63	50	<b>198 335 108</b>	1.303	<b>198 335 128</b>	1.190	<b>198 335 148</b>	1.248
1500 - 15000	63	50	<b>198 335 109</b>	1.297	<b>198 335 129</b>	1.351	<b>198 335 149</b>	1.409
2000 - 20000	75	65	<b>198 335 110</b>	2.508	<b>198 335 130</b>	2.378	<b>198 335 150</b>	2.441
3000 - 30000	75	65	<b>198 335 111</b>	2.477	<b>198 335 131</b>	2.472	<b>198 335 151</b>	2.377
8000 - 60000	75	65	<b>198 335 112</b>	2.294	<b>198 335 132</b>	2.150	<b>198 335 152</b>	2.150

Scale range (L/h)	D (mm)	L (mm)	L1 (mm)	L2 (mm)	G (inch)
50 - 500	58	385	341	335	1 ½
100 - 1000	58	385	341	335	1 ½
150 - 1500	72	393	341	335	2
250 - 2500	72	393	341	335	2
200 - 2000	83	403	341	335	2 ¼
300 - 3000	83	403	341	335	2 ¼
600 - 6000	83	403	341	335	2 ¼
600 - 6000	101	417	341	335	2 ¾
1000 - 10000	101	417	341	335	2 ¾
1500 - 15000	101	417	341	335	2 ¾
2000 - 20000	135	429	341	335	3 ½
3000 - 30000	135	429	341	335	3 ½
8000 - 60000	135	429	341	335	3 ½

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>