



L = length / Länge

## Electrofusion saddle

- PE 100 SDR 11 (ISO S5)
  - 10 bar Gas / 16 bar Water
  - Complete with lower part
  - \* Complete with moulded-on lower part
  - 4 mm pin connectors
  - Limited path fusion indicators
  - \*\*Delivery without lower part for assembling as Top Load with tool no. 799.350.477
- Not suitable for all tapping-tees, tapping-valves and spigots with cutter of the modular systems;  
SDR compatibility according to individual parts

|    | d<br>(mm) | d1<br>(mm) | Code               | SP | Weight<br>(kg) | L<br>(mm) |
|----|-----------|------------|--------------------|----|----------------|-----------|
|    | 63        | 63         | <b>193 131 037</b> | 1  | 0.325          | 165       |
|    | 75        | 63         | <b>193 131 047</b> | 1  | 0.455          | 165       |
|    | 90        | 63         | <b>193 131 057</b> | 1  | 0.415          | 165       |
|    | 110       | 63         | <b>193 131 067</b> | 1  | 0.458          | 165       |
| *  | 110       | 63         | <b>193 133 067</b> | 1  | 0.490          | 182       |
|    | 125       | 63         | <b>193 131 077</b> | 1  | 0.502          | 165       |
|    | 140       | 63         | <b>193 131 087</b> | 1  | 0.523          | 165       |
|    | 160       | 63         | <b>193 131 097</b> | 1  | 0.493          | 165       |
| *  | 160       | 63         | <b>193 133 097</b> | 1  | 0.543          | 182       |
|    | 180       | 63         | <b>193 131 107</b> | 1  | 0.600          | 165       |
|    | 200       | 63         | <b>193 131 117</b> | 1  | 0.634          | 165       |
|    | 225       | 63         | <b>193 131 127</b> | 1  | 0.618          | 165       |
|    | 250       | 63         | <b>193 131 137</b> | 1  | 0.627          | 165       |
| ** | 280       | 63         | <b>193 131 147</b> | 1  | 0.359          | 165       |
| ** | 315 - 355 | 63         | <b>193 131 157</b> | 1  | 0.373          | 165       |
| ** | 400       | 63         | <b>193 131 177</b> | 1  | 0.356          | 165       |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>