



## Adaptor socket nipple ABS metric R

### Model:

- With solvent cement spigot/socket metric and taper male thread R
- Connection for plastic threads
- Do not use thread sealing pastes that are harmful to ABS

PN (bar)	d (mm)	R (inch)	d1 (mm)	Code	SP	Weight (kg)	closest inch (inch)	z (mm)	z1 (mm)	s (mm)
10	16	½	20	<b>729 910 556</b>	10	0.012	⅜	42	28	32
10	20	¾	25	<b>729 910 557</b>	10	0.017	½	47	31	36
10	25	1	32	<b>729 910 558</b>	10	0.030	¾	54	35	46
10	32	1 ¼	40	<b>729 910 559</b>	10	0.046	1	60	38	55
10	40	1 ½	50	<b>729 910 560</b>	10	0.072	1 ¼	66	40	65
10	50	2	63	<b>729 910 561</b>	5	0.125	1 ½	78	47	80

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>