



## Tapping saddle Monobloc version

- PE 100 SDR 11 (ISO S5)
- 10 bar Gas / 16 bar Water
- With integrated cutter to tap live mains under pressure
- Complete with moulded-on lower part
- 4 mm pin connectors
- Limited path fusion indicators
- Long fusion outlet
- O-ring-sealed screw cap
- \*Compatible with GASSTOP type GS

	d	d1	Code	SP	GP	Weight	d2	H	H1	L	L1	z
	(mm)	(mm)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
*	63	20	<b>193 131 932</b>	1	20	0.368	25	146	44	144	76	110
	63	25	<b>193 131 933</b>	1	20	0.393	25	146	44	144	76	110
*	63	32	<b>193 131 934</b>	1	20	0.376	25	146	44	144	76	110
*	90	20	<b>193 131 952</b>	1	12	0.494	32	198	61	162	76	115
	90	25	<b>193 131 953</b>	1	12	0.503	32	198	61	162	76	115
*	90	32	<b>193 131 954</b>	1	12	0.505	32	198	61	162	76	115
	90	63	<b>193 131 957</b>	1	10	0.667	32	198	61	162	76	115
*	110	20	<b>193 131 962</b>	1	9	0.560	32	208	71	162	76	115
	110	25	<b>193 131 963</b>	1	9	0.570	32	208	71	162	76	115
*	110	32	<b>193 131 964</b>	1	9	0.574	32	208	71	162	76	125
	110	63	<b>193 131 967</b>	1	8	0.684	32	208	71	162	100	160
*	125	20	<b>193 131 972</b>	1	6	0.562	32	216	79	162	76	120
	125	25	<b>193 131 973</b>	1	6	0.552	32	216	79	162	76	120
*	125	32	<b>193 131 974</b>	1	6	0.574	32	216	79	162	76	120
	125	63	<b>193 131 977</b>	1	6	0.704	32	216	79	162	76	120
*	160	20	<b>193 131 992</b>	1	6	0.631	32	233	96	162	76	120
	160	25	<b>193 131 993</b>	1	6	0.641	32	233	96	162	76	125
*	160	32	<b>193 131 994</b>	1	6	0.648	32	233	96	162	76	130
	160	63	<b>193 131 997</b>	1	6	0.794	32	233	96	162	100	170

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>