



## Elbow 45° ABS metric

- >d225 - maximum operating temperature: +40°C

d (inch)	d (mm)	PN (bar)	Code	SP	Weight (kg)	closest inch (inch)	z (mm)	D (mm)	L (mm)
	20	16	<b>729 150 106</b>	10	0.009	½	5	25	21
	25	16	<b>729 150 107</b>	10	0.013	¾	6	31	25
	32	10	<b>729 150 108</b>	10	0.026	1	8	40	30
	40	10	<b>729 150 109</b>	10	0.044	1 ¼	10	49	36
	50	10	<b>729 150 110</b>	5	0.079	1 ½	12	61	43
	63	10	<b>729 150 111</b>	10	0.143	2	14	76	52
2 ½	75	10	<b>729 150 112</b>	5	0.225	2 ½	17	89	61
	90	10	<b>729 150 113</b>	4	0.363	3	20	107	71
	110	10	<b>729 150 114</b>	10	0.567	4	28	131	89
5	140	10	<b>729 150 116</b>	1	1.175	5	32	162	108
	160	10	<b>729 150 117</b>	4	1.713	6	36	185	122
	200	10	<b>729 150 119</b>	1	2.546	8	43	225	149
	225	10	<b>729 150 120</b>	1	3.162	8	49	250	168
	250	6	<b>729 150 121</b>	1	6.139	9	60	282	192
	280	6	<b>729 150 122</b>	1	10.500	10	66	318	213
	315	6	<b>729 150 123</b>	1	14.600	12	74	356	239

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>