



Type A



Type B



Installation fitting type 313 pre-insulated ABS metric

Model:

- Insulation made from PUR
- Outer jacket impact resistant. Color: black
- With 1/2 " Rp threaded branch for sensors (i.e. pressure)
- Outer jacket impact resistant. Color: black

Range of use:

- compatible signet pressure sensors: type 2450-1 /-2 /-5

d (mm)	D (mm)	PN (bar)	Code	SP	Weight (kg)
25	90	10	738 313 007	1	0.330
32	90	10	738 313 008	2	0.400
40	110	10	738 313 009	1	0.500
50	110	10	738 313 010	1	0.570
63	125	10	738 313 011	1	0.890
75	140	10	738 313 012	1	0.767
90	160	10	738 313 013	1	0.961
110	180	10	738 313 114	1	1.178
140	225	10	738 313 116	1	1.731
160	250	10	738 313 117	1	2.228
200	280	10	738 313 119	0	3.609
225	315	10	738 313 120	1	4.645

d (mm)	Rp (inch)	L (mm)	H (mm)	z (mm)	required Nipple	closest inch (inch)	Type
25	½	160	112	80	2x738901607	¾	A
32	½	180	112	90	2x738901608	1	A
40	½	180	112	90	2x738901609	1 ¼	A
50	½	180	112	90	2x738901610	1 ½	A
63	½	200	100	100	2x738901611	2	A
75	½	250	147	125	2x738901612	2 ½	A
90	½	280	162	140	2x738901613	3	A
110	½	220	119	110	2x738901114	4	B
140	½	220	134	110	2x738901116	5	B
160	½	220	145	110	2x738901117	6	B
200	½	250	165	125	2x738901119	8	B
225	½	280	178	140	2x738901120	8	B

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>