



## Bend 90° pre-insulated ABS metric

### Model:

- Insulation made from PUR
- Outer jacket impact resistant. Color: black

Connecting dimensions = Pipe outer diameter

\* Available as long as our stock will last

d (mm)	PN (bar)	D (mm)	Code	SP	Weight (kg)	z (mm)	L (mm)	required Nipple	closest inch (inch)
25	10	90	<b>738 001 107</b>	1	0.183	69	69	738901607	¾
32	10	90	<b>738 001 108</b>	1	0.220	86	86	738901608	1
40	10	110	<b>738 001 109</b>	1	0.363	109	109	738901609	1 ¼
50	10	110	<b>738 001 110</b>	1	0.498	131	131	738901610	1 ½
63	10	125	<b>738 001 111</b>	1	0.759	164	164	738901611	2
75	10	140	<b>738 001 112</b>	1	1.159	194	194	738901612	2 ½
90	10	160	<b>738 001 113</b>	1	1.885	231	231	738901613	3
110	10	180	<b>738 001 114</b>	1	3.235	281	281	738901614	4
140	10	225	<b>738 001 116</b>	1	6.909	356	356	738901616	5
160	10	250	<b>738 001 117</b>	1	6.000	406	406	738901617	6
225	10	315	<b>738 001 120</b>	1	8.176	287	287	738901620	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>