


Datasheet

Threaded central offtake tee Rp PVC-U



| d [mm] | Rp [inch] | d [inch] | PN | Code | SP | GP | kg | L1 [mm] | L2 [mm] | Z1 [mm] | Z2 [mm] | E [mm] |
|-----------|--------------|-------------|----|------------------|----|-----|-------|------------|------------|------------|------------|-----------|
| 16 | 3/8 | | 16 | RV0TIP16A | 10 | 280 | 0.017 | 14 | 11.4 | 9 | 11.6 | 23 |
| 20 | 1/2 | | 16 | RV0TIP20B | 10 | 150 | 0.028 | 16 | 15.0 | 11 | 12.0 | 28 |
| 25 | 3/4 | | 16 | RV0TIP25C | 10 | 100 | 0.046 | 19 | 16.3 | 14 | 16.7 | 34 |
| 32 | 1 | | 16 | RV0TIP32D | 10 | 130 | 0.076 | 22 | 19.1 | 17 | 19.9 | 42 |
| 40 | 1 1/4 | | 16 | RV0TIP40E | 90 | - | 0.120 | 26 | 21.4 | 21 | 25.6 | 51 |
| 50 | 1 1/2 | | 16 | RV0TIP50F | 50 | - | 0.200 | 31 | 21.4 | 26 | 35.6 | 61 |
| 63 | 2 | | 16 | RV0TIP63G | 25 | - | 0.355 | 38 | 25.7 | 33 | 45.3 | 75 |
| 75 | 2 1/2 | 2 1/2 | 16 | RV0TIP75H | 35 | - | 0.540 | 44 | 30.2 | 39 | 52.8 | 89 |
| 90 | 3 | | 16 | RV0TIP90I | 24 | - | 0.850 | 51 | 33.3 | 47 | 64.7 | 106 |
| 110 | 4 | | 16 | RV0TIP91L | 14 | - | 1.440 | 61 | 39.3 | 57 | 78.7 | 129 |

PF 2 01 951 011