


## TP Reducing socket PVC-U metric

• (\*) with octagon



	<b>d</b>	<b>d1</b>	<b>PN</b>	<b>Code</b>	<b>SP</b>	<b>Weight</b>	<b>Z</b>	<b>E2</b>	<b>E1</b>	<b>L2</b>	<b>L1</b>
	(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
	20	16	16	<b>RV0MRI20A</b>	1	0.010	6	23	28	14	16
	25	20	16	<b>RV0MRI25B</b>	1	0.016	6	28	34	16	19
	32	25	16	<b>RV0MRI32C</b>	1	0.026	6	34	42	19	22
	40	32	16	<b>RV0MRI40D</b>	1	0.053	6	42	51	22	26
	50	40	16	<b>RV0MRI50E</b>	1	0.080	6	51	61	26	31
	63	50	16	<b>RV0MRI63F</b>	1	0.100	6	61	75	31	38
*	75	63	16	<b>RV0MRI75G</b>	1	0.216	4	75	89	38	44
*	90	75	16	<b>RV0MRI90H</b>	1	0.347	5	89	106	44	51
*	110	90	16	<b>RV0MRI91I</b>	1	0.563	6	106	129	51	61
	125	110	16	<b>RV0MRI92L</b>	1	0.736	24	129	145	61	69
	140	110	16	<b>RV0MRI93L</b>	1	0.982	25	129	160	61	76
	140	125	16	<b>RV0MRI93M</b>	1	1.022	19	145	160	69	76
	160	110	16	<b>RV0MRI94L</b>	1	1.200	24	130	181	61	86
	160	140	16	<b>RV0MRI94N</b>	1	1.300	8	170	180	76	86
	200	160	16	<b>RV0MRI96O</b>	1	2.333	24	184	227	86	106
	225	200	10	<b>RV0MRI97Q</b>	4	6.459	10	227	255	106	119

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>