




**Double union safeblock B.S.P. PVC-U
Ball valve with threaded sockets G**



d1 (inch)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	Z (mm)	X (mm)	M (mm)	S (mm)	A (mm)	L2 (mm)	H (mm)	L1 (mm)
3/8	10	16	VSA22F160	1	0.127	48	42	40	19	50	76	53	14
1/2	15	16	VSA22F200	150	0.127	48	42	40	19	50	80	53	16
3/4	20	16	VSA22F250	100	0.202	53	48	45	19	59	91	60	19
1	25	16	VSA22F320	60	0.292	58	54	51	21	68	102	67	22
1 1/4	32	16	VSA22F400	36	0.439	68	62	59	25	80	120	79	26
1 1/2	40	16	VSA22F500	24	0.685	78	72	70	27	94	140	90	31
2	50	16	VSA22F630	16	1.160	93	86	84	29	115	169	107	38
2 1/2	65	10	VSA22F750	8	2.141	118	110	103	32	145	206	129	44
3	80	10	VSA22F900	1	3.220	140	128	120	36	168	242	143	51
4	100	10	VSA22F910	1	5.764	160	150	141	43	210	282	169	61

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>