



Multi/Clamp Flange (tapping sleeve)
length 500 mm

Model:

- Suitable for all kinds of pipe material. For use on plastic pipes please consult Georg Fischer Waga N.V.
- Double band saddle with flanged outlet
- Full circle construction for optimal pipe support
- To obtain the total product price, please take the price of the tapping sleeve and add the price for the flange outlet
- All metal parts are stainless steel, quality AISI 304 (on request AISI 316)
- The rubber gasket is available in NBR (EPDM on request)
- Water and gas: NBR according to EN 682 (-10°C up to +70°C); potable water: EPDM according to EN 681-1 (-10°C up to +55°C)
- For working pressures in GAS please consult Georg Fischer Waga N.V.
- To choose the correct length of Multi/Clamp check our technical information

Range (mm)	DN (mm)	PN Water (bar)	NBR Code
95 - 104		16.0	95-104L500N
98 - 108		16.0	98-108L500N
108 - 128		16.0	108-128L500N
118 - 138		16.0	118-138L500N
133 - 153		16.0	133-153L500N
143 - 163		16.0	143-163L500N
160 - 180		16.0	160-180L500N
180 - 200		16.0	180-200L500N
190 - 210		16.0	190-210L500N
210 - 230		16.0	210-230L500N
230 - 250		16.0	230-250L500N
240 - 260		16.0	240-260L500N
250 - 270		16.0	250-270L500N
270 - 290		16.0	270-290L500N
290 - 310		16.0	290-310L500N
315 - 335		16.0	315-335L500N
335 - 355		16.0	335-355L500N
-	350	16.0	DN350L500N
-	400	16.0	DN400L500N
-	450	16.0	DN450L500N
-	500	16.0	DN500L500N
-	600	10.0	DN600L500N
-	700		DN700L500N
-	750		DN750L500N
-	800		DN800L500N

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>