


Reducers



ELGEF Plus Reducer PE100 d20-63mm / SDR11 / with integral pipe fixation

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators




d (mm)	d2 (mm)	DN (mm)	PN (bar)	SDR	Code	Weight (kg)	d1 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)	SDR pipe
25	20	20	16	11	753 901 639	0.051	35	74	34	34	6	9-11
32	20	25	16	11	753 901 640	0.056	44	79	33	36	10	9-11
32	25	25	16	11	753 901 641	0.062	44	79	33	36	10	9-11
40	20	32	16	11	753 901 644	0.069	54	88	33	39	15	9-11
40	25	32	16	11	753 901 645	0.084	54	88	33	39	15	9-11
40	32	32	16	11	753 901 646	0.095	54	88	33	39	13	9-11
50	32	40	16	11	753 901 651	0.124	66	96	35	43	18	9-11
50	40	40	16	11	753 901 652	0.119	66	96	39	43	14	9-11
63	32	50	16	11	753 901 656	0.158	81	105	35	48	23	9-11
63	40	50	16	11	753 901 657	0.176	81	105	39	48	19	9-11
63	50	50	16	11	753 901 658	0.176	81	105	43	48	15	9-11



ELGEF Plus Reducer PE100 d63-180mm / SDR11

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators




d (mm)	d2 (mm)	DN (mm)	PN (bar)	SDR	Code	Weight (kg)	d1 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)	SDR pipe
90	63	80	16	11	753 901 831	0.385	113	146	63	47	36	9-17.6
110	63	100	16	11	753 901 832	0.644	140	184	71	58	55	9-11
110	90	100	16	11	753 901 833	0.700	138	173	73	63	38	9-17.6
125	90	100	16	11	753 901 836	0.891	152	194	77	62	55	9-17.6
160	90	150	16	11	753 901 839	1.600	202	227	90	72	65	9-17.6
160	110	150	16	11	753 901 864	1.783	202	226	90	71	65	9-17.6
180	125	150	16	11	753 901 865	2.340	225	254	96	78	80	9-17.6



ELGEF Plus Reducer PE100 d200/160-250/225mm / SDR11

- 10 bar Gas / 16 bar Water
- 4 mm pin connectors
- Limited path fusion indicators
- Two separate fusion zones



d (mm)	d2 (mm)	DN (mm)	PN (bar)	SDR	Code	Weight (kg)	d1 (mm)	L (mm)	L1 (mm)	L2 (mm)	z (mm)	SDR pipe
200	160	200	16	11	753 901 837	5.098	250	365	104	90	171	11-26
225	160	200	16	11	753 901 838	6.000	280	385	112	90	183	11-26
225	200	200	16	11	753 901 845	8.200	280	390	112	104	173	11-26
250	160	250	16	11	753 901 840	7.860	310	400	123	90	187	11-26
250	200	250	16	11	753 901 841	8.480	310	417	123	104	200	11-26
250	225	250	16	11	753 901 842	8.450	310	430	123	112	204	11-26