


TP Threaded fixed flange Rp PVC-U



- Maximum medium- or ambient temperature 45°



Rp	DN	PN	Code	SP	Weight	Z	E	I	S	f	L
(inch)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
½	15	10	RV0FFF200	100	0.077	5.5	95	65	11	14	15.0
¾	20	10	RV0FFF250	70	0.101	7.5	105	75	12	14	16.3
1	25	10	RV0FFF320	120	0.142	7.5	115	85	14	14	19.1
1 ¼	32	10	RV0FFF400	60	0.223	9.0	140	100	15	18	21.4
1 ½	40	10	RV0FFF500	50	0.281	14.0	150	110	16	18	21.4
2	50	10	RV0FFF630	1	0.420	17.0	165	125	18	18	25.7
2 ½	65	10	RV0FFF750	20	0.516	20.0	185	145	19	18	30.2
3	80	10	RV0FFF900	1	0.708	25.0	200	160	20	18	30.3
4	100	10	RV0FFF910	1	0.890	30.0	220	180	22	18	39.9

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>