


TP Fixed flange PVC-U metric



- **DN** indicates the nominal diameter of the PVC pipe
- Bolt holes PN10
- Maximum medium- or ambient temperature 45°



d (mm)	d (inch)	DN (mm)	PN (bar)	Code	SP	GP	Weight (kg)	L (mm)	S (mm)	f (mm)	E (mm)	I (mm)	Z (mm)
20		15	10	RV0FFI200	1	100	0.077	16	11	14	95	65	4.5
25		20	10	RV0FFI250	1	70	0.103	19	12	14	105	75	4.5
32		25	10	RV0FFI320	1	120	0.142	22	14	14	115	85	4.5
40		32	10	RV0FFI400	1	60	0.223	26	15	18	140	100	4.5
50		40	10	RV0FFI500	1	50	0.265	31	16	18	150	110	4.5
63		50	10	RV0FFI630	1	40	0.368	38	18	18	165	125	4.5
75	2 ½	65	10	RV0FFI750	1	20	0.501	44	19	18	185	145	6.0
90		80	10	RV0FFI900	1	15	0.687	51	20	18	200	160	7.0
110		100	10	RV0FFI910	1	10	0.940	61	22	18	220	180	8.0
125		110	10	RV0FFI920	1	6	1.032	69	24	18	230	190	7.0
140	5	125	10	RV0FFI930	1	6	1.335	76	26	18	250	210	7.0
160		140	10	RV0FFI940	1	5	1.835	86	28	18	285	240	7.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>