




## TP Threaded reducing socket Rp-Rp PVC-U

d (inch)	Rp1 (inch)	PN (bar)	Code	SP	GP	Weight (kg)	L2 (mm)	L1 (mm)	E1 (mm)	E2 (mm)	Z (mm)
½	¾	16	<b>RV0MRF20A</b>	10	250	0.015	11.4	15.0	28	23	6
¾	1½	16	<b>RV0MRF25B</b>	10	200	0.024	15.0	16.3	34	28	7
1	¾	16	<b>RV0MRF32C</b>	10	120	0.038	16.3	19.1	42	34	7
1 ¼	1	16	<b>RV0MRF40D</b>	1	190	0.059	19.1	21.4	51	42	8
1 ½	1 ¼	16	<b>RV0MRF50E</b>	1	165	0.050	21.4	21.4	58	51	8
2	1 ½	16	<b>RV0MRF63F</b>	1	80	0.116	21.4	25.7	72	58	8
2 ½	2	16	<b>RV0MRF75G</b>	1	130	0.200	25.7	30.2	89	72	8
3	2 ½	16	<b>RV0MRF90H</b>	1	80	0.265	30.2	33.3	103	89	9
4	3	16	<b>RV0MRF91I</b>	1	54	0.426	33.3	39.3	130	103	10



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>