




Single union safeblock B.S.P. PVC-U
Ball valve with female threaded socket G/male thread R

d1 (inch)	R (inch)	PN (bar)	EPDM Code	SP	Weight (kg)	A (mm)	S (mm)	Z (mm)	M (mm)	L1 (mm)	L2 (mm)	L (mm)	H (mm)
3/8	3/8	16	VSA18S160	180	0.096	50	19	53	40	12.0	67	14	53
1/2	1/2	16	VSA18S200	180	0.096	50	19	55	40	15.0	71	16	53
3/4	3/4	16	VSA18S250	120	0.152	59	19	61	45	16.5	80	19	60
1	1	16	VSA18S320	75	0.225	68	21	68	51	19.5	90	22	67
1 1/4	1 1/4	16	VSA18S400	45	0.340	80	25	84	59	21.5	110	26	79
1 1/2	1 1/2	16	VSA18S500	30	0.500	94	27	97	70	21.5	128	31	90
2	2	16	VSA18S630	18	0.845	115	29	119	84	25.5	157	38	107



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>