



## MULTI/JOINT® 3187 Plus Wide Range Reduced spigot end, restraint, Uni/Fiksers

### Model:



- Suitable for all kinds of pipe material
- Suitable for water and gas (EPDM only for potable water)
- Ductile iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- Hygiene protection included DN50 - DN1025

### Installation instruction:

- Read the user manual
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information

### Note:

ID min. = minimum insertion depth



DN (mm)	d3 (mm)	Range 1 (mm)	NBR / A2 Code	EPDM / A2 Code	Weight (kg)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
80	110	84 - 105	709 345 224	709 345 624	5.900	709 345 024	709 345 324	5.900

DN (mm)	d3 (mm)	Min. (mm)	Max. (mm)	b (mm)	ID min. (mm)	e (mm)	M	l (mm)	PN Water (bar)	MOP Gas (bar)
80	110	242	264	210	84	3	M12	120	16	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>