



MULTI/JOINT® 3407 Plus Wide Range Bend, restraint, Uni/Fiksers

Model:



- Suitable for all kinds of pipe material
- Suitable for water and gas (EPDM only for potable water)
- Ductile iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- Hygiene protection included DN50 - DN1025

Installation instruction:

- Read the user manual
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information

Note:

ID min. = minimum insertion depth



DN (mm)	Range 1 (mm)	Range 3 (mm)	NBR / A2 Code	EPDM / A2 Code	Weight (kg)
80	84 - 105	84 - 105	709 475 214	709 475 614	10.000
100	104 - 132	104 - 132	709 475 216	709 475 616	13.400
150	154 - 192	154 - 192	709 475 220	709 475 620	25.600

DN (mm)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
80	709 475 014	709 475 314	10.000
100	709 475 016	709 475 316	13.400
150	709 475 020	709 475 320	25.600

DN (mm)	Min. (mm)	Max. (mm)	b (mm)	ID min. (mm)	e (mm)	M	f (mm)	PN Water (bar)	MOP Gas (bar)
80	300	322	210	84	3	M12	100	16	8
100	359	385	241	90	3	M16	125	16	8
150	441	478	312	110	4	M16	175	16	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>