


TP Reduced tee 90° PVC-U metric



d (mm)	d1 (mm)	PN (bar)	Code	SP	GP	Weight (kg)	Z1 (mm)	Z2 (mm)	L1 (mm)	L2 (mm)	E2 (mm)	E1 (mm)
20	16	16	RV0TRI20A	10	200	0.024	11	11	16	14	23	28
25	16	16	RV0TRI25A	10	120	0.039	14	14	19	14	23	34
25	20	16	RV0TRI25B	10	120	0.040	14	14	19	16	28	34
32	16	16	RV0TRI32A	10	140	0.063	17	17	22	14	23	42
32	20	16	RV0TRI32B	10	140	0.068	17	17	22	16	28	42
32	25	16	RV0TRI32C	10	140	0.068	17	17	22	19	34	42
40	20	16	RV0TRI40B	1	100	0.107	21	21	26	16	28	51
40	25	16	RV0TRI40C	1	100	0.108	21	21	26	19	34	51
40	32	16	RV0TRI40D	1	100	0.112	21	21	26	22	42	51
50	20	16	RV0TRI50B	1	50	0.155	26	26	31	16	28	61
50	25	16	RV0TRI50C	1	50	0.160	26	26	31	19	34	61
50	32	16	RV0TRI50D	1	50	0.161	26	26	31	22	42	61
50	40	16	RV0TRI50E	1	50	0.173	26	26	31	26	51	61
63	20	16	RV0TRI63B	1	30	0.257	33	33	38	16	28	75
63	25	16	RV0TRI63C	1	30	0.262	33	33	38	19	34	75
63	32	16	RV0TRI63D	1	30	0.274	33	33	38	22	42	75
63	40	16	RV0TRI63E	1	30	0.270	33	33	38	26	51	75
63	50	16	RV0TRI63F	1	30	0.278	33	33	38	31	61	75
75	32	16	RV0TRI75D	1	18	0.455	39	39	44	22	42	89
75	40	16	RV0TRI75E	1	45	0.460	39	39	44	26	51	89
75	50	16	RV0TRI75F	1	18	0.458	39	39	44	31	61	89
75	63	16	RV0TRI75G	1	30	0.471	39	39	44	38	75	89
90	40	16	RV0TRI90E	1	30	0.692	47	47	51	26	61	106
90	50	16	RV0TRI90F	1	28	0.703	47	47	51	31	61	106
90	63	16	RV0TRI90G	1	24	0.707	47	47	51	38	75	106
90	75	16	RV0TRI90H	1	24	0.731	47	47	51	44	89	106
110	50	16	RV0TRI91F	1	16	1.228	57	57	61	31	61	129
110	63	16	RV0TRI91G	1	16	1.231	57	57	61	38	75	129
110	75	16	RV0TRI91H	1	16	1.245	57	57	61	44	89	129
110	90	16	RV0TRI91I	1	14	1.302	57	57	61	51	106	129
125	63	16	RV0TRI92G	1	9	1.955	66	66	69	38	75	148
125	90	16	RV0TRI92I	1	9	1.737	66	66	69	51	106	148
125	110	16	RV0TRI92L	1	8	1.827	66	66	69	61	129	148
160	90	16	RV0TRI94I	1	4	3.771	82	82	86	51	106	190
160	110	16	RV0TRI94L	1	4	3.819	82	82	86	61	129	190

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>