




**Check valve ISO PVC-U**  
With solvent cement sockets

**Model:**

- Rubber spring
- (\*)Body and dimensions = 3"



	d	d	DN	PN	EPDM	SP	Weight	L1	L2	A	X	Z
	(mm)	(inch)	(mm)	(bar)	Code		(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
	16		10	16	<b>VR0211160</b>	1	0.133	14	76	50	42	48
	20		15	16	<b>VR0211200</b>	1	0.125	16	80	50	42	48
	25		20	16	<b>VR0211250</b>	1	0.196	19	91	59	48	53
	32		25	16	<b>VR0211320</b>	1	0.245	22	102	68	54	58
	40		32	16	<b>VR0211400</b>	1	0.375	26	120	80	62	68
	50		40	16	<b>VR0211500</b>	1	0.610	31	140	94	72	78
	63		50	16	<b>VR0211630</b>	1	1.030	38	169	115	86	93
*	75	2 ½	65	10	<b>VR0211750</b>	1	3.028	44	206	168	110	118
	90		80	10	<b>VR0211900</b>	1	3.054	51	242	168	128	140

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>