




**Check valve B.S.P. PVC-U  
With threaded sockets G**

- (\*)Body and dimensions = 3"

**Model:**

- Rubber spring



	d1 (inch)	DN (mm)	PN (bar)	EPDM Code	SP	Weight (kg)	L2 (mm)	A (mm)	L1 (mm)	X (mm)	Z (mm)
	3/8	10	16	<b>VRO21F160</b>	1	0.136	76	50	14	42	48
	1/2	15	16	<b>VRO21F200</b>	1	0.125	80	50	16	42	48
	3/4	20	16	<b>VRO21F250</b>	1	0.193	91	59	19	48	53
	1	25	16	<b>VRO21F320</b>	1	0.273	102	68	22	54	58
	1 1/4	32	16	<b>VRO21F400</b>	1	0.392	116	80	24	62	68
	1 1/2	40	16	<b>VRO21F500</b>	1	0.605	126	94	24	72	78
	2	50	16	<b>VRO21F630</b>	1	1.023	149	115	28	86	93
*	2 1/2	65	10	<b>VRO21F750</b>	1	2.977	184	168	33	128	118
	3	80	10	<b>VRO21F900</b>	1	3.051	212	168	36	128	140

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>