


## TP Threaded adaptor GAS PVC-U 3 diameters



d1 (mm)	d2 (mm)	d3 (inch)	PN (bar)	Code	SP	GP	Weight (kg)	O (mm)	L3 (mm)	L1 (mm)	H (mm)	L2 (mm)
12	16	3/8	16	<b>RV0AMP12A</b>	10	600	0.008	22	11.4		36	14
16	20	3/8	16	<b>RV0AMP16A</b>	10	500	0.010	24	11.4	14	40	16
16	20	1/2	16	<b>RV0AMP16B</b>	10	400	0.011	24	15.0	14	43	16
20	25	3/8	16	<b>RV0AMP20A</b>	10	300	0.013	30	11.4	16	43	19
20	25	1/2	16	<b>RV0AMP20B</b>	10	300	0.014	30	15.0	16	46	19
20	25	3/4	16	<b>RV0AMP20C</b>	10	300	0.015	30	16.3	16	47	19
25	32	1/2	16	<b>RV0AMP25B</b>	10	200	0.025	36	15.0	19	49	22
25	32	3/4	16	<b>RV0AMP25C</b>	10	200	0.026	36	16.3	19	50	22
25	32	1	16	<b>RV0AMP25D</b>	10	200	0.029	36	19.1	19	53	22
32	40	3/4	16	<b>RV0AMP32C</b>	10	140	0.037	42	16.3	22	54	26
32	40	1	16	<b>RV0AMP32D</b>	10	120	0.038	42	19.1	22	57	26
32	40	1 1/4	16	<b>RV0AMP32E</b>	10		0.048	46	21.4	22	60	26
40	50	1	16	<b>RV0AMP40D</b>	90		0.068	55	19.1	26	64	31
40	50	1 1/4	16	<b>RV0AMP40E</b>	50		0.072	55	21.4	26	67	31
40	50	1 1/2	16	<b>RV0AMP40F</b>	80		0.071	55	21.4	26	67	31
50	63	1 1/4	16	<b>RV0AMP50E</b>	50		0.114	65	21.4	31	74	38
50	63	1 1/2	16	<b>RV0AMP50F</b>	110		0.113	65	21.4	31	74	38
50	63	2	16	<b>RV0AMP50G</b>	100		0.122	65	25.7	31	78	38
63	75	1 1/2	16	<b>RV0AMP63F</b>	35		0.139	80	21.4	38	80	44
63	75	2	16	<b>RV0AMP63G</b>	70		0.150	80	25.7	38	84	44
63	75	2 1/2	16	<b>RV0AMP63H</b>	50		0.170	80	30.2	38	91	44
75	90	2	16	<b>RV0AMP75G</b>	54		0.266	95	25.7	44	94	51
75	90	2 1/2	16	<b>RV0AMP75H</b>	60		0.270	95	30.2	44	99	51
75	90	3	16	<b>RV0AMP75I</b>	36		0.281	95	33.3	44	102	51
90	110	2 1/2	16	<b>RV0AMP90H</b>	25		0.465	115	30.2	51	110	61
90	110	3	16	<b>RV0AMP90I</b>	25		0.486	115	33.3	51	113	61
90	110	4	16	<b>RV0AMP90L</b>	16		0.487	115	39.3	51	118	61
110	125	3	10	<b>RV0AMP91I</b>	40		0.480	130	33.3	61	115	66
110	125	4	10	<b>RV0AMP91L</b>	32		0.480	130	39.3	61	120	66
110	125	5	10	<b>RV0AMP91N</b>	32		0.533	130	40.0	61	120	66
125	140	5	10	<b>RV0AMP92N</b>	24		0.609		74.0	69	145	71

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>