


TP Plain/threaded socket Rp PVC-U



- (*) Without octagon

	d	d	Rp	PN	Code	SP	GP	Weight	E2	E1	L1	L2	Z
	(mm)	(inch)	(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
	16		3/8	16	RV0MAP16A	10	500	0.009	23	23	14	11.4	6
	20		1/2	16	RV0MAP20B	10	250	0.017	28	28	16	15.0	6
	25		3/4	16	RV0MAP25C	10	200	0.024	34	34	19	16.3	6
	32		1	16	RV0MAP32D	10	130	0.042	42	42	22	19.1	6
	40		1 1/4	16	RV0MAP40E	1	100	0.059	51	51	26	21.4	4
	50		1 1/2	16	RV0MAP50F	1	60	0.093	58	61	31	21.4	7
	63		2	16	RV0MAP63G	1	80	0.128	72	75	38	25.7	7
	75	2 1/2	2 1/2	16	RV0MAP75H	1	110	0.215	89	89	44	30.2	8
	90		3	16	RV0MAP90I	1	64	0.337	103	106	51	33.3	9
	110		4	16	RV0MAP91L	1	35	0.535	130	129	61	39.3	10
*	125		5	16	RV0MAP92N	1	16	1.111		160	69	43.6	51
*	140	5	5	16	RV0MAP93N	1	9	1.185		162	76	43.6	40
*	160		6	16	RV0MAP94O	9	9	1.390		184	86	48.0	46

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>