



MULTI/JOINT® 3557 Plus Wide Range Reduced duckfoot, restraint, Uni/Fiksers

Model:

- Suitable for all kinds of pipe material
- Suitable for water and gas (EPDM only for potable water)
- Ductile iron GGG45 body and clamping ring(s), acc. to EN-GJS-450-10
- RESICOAT® epoxy powder coating, according to GSK standards and EN 14901
- NBR or EPDM gasket, NBR acc. to EN 682 (-5°C up to +50°C), EPDM acc. to EN 681-1 (0°C up to +50°C)
- Angular deflection of max. 8° per socket at installation (based on the middle of the range)
- Stainless steel A4 quality (AISI 316) Uni/Fiksers
- Stainless steel A2 quality (AISI 304) or A4 quality (AISI 316) bolts, nuts and washers
- Threaded outlet 2 inch
- Hygiene protection included DN50 - DN1025

Installation instruction:

- Read the user manual
- For restraint versions, on plastic pipes, the use of an insert stiffener (see accessories) is mandatory, check our technical information

Note:

ID min. = minimum insertion depth

Thread Type	Size (inch)	DN (mm)	DN-DN (mm)	Range 1 (mm)	Flange 3 (mm)	Drilling pattern
Rp	2	65	65 - 80	63 - 90	80	PN10
Rp	2	65	65 - 80	63 - 90	80	PN16
Rp	2	100	100 - 80	104 - 132	80	PN16
Rp	2	125	125 - 80	132 - 155	80	PN10
Rp	2	125	125 - 80	132 - 155	80	PN16
Rp	2	150	150 - 80	154 - 192	80	PN10
Rp	2	150	150 - 80	154 - 192	80	PN16

NBR / A2 Code	EPDM / A2 Code	Weight (kg)	NBR / A4 Code	EPDM / A4 Code	Weight (kg)
709 495 236	709 495 636	13.300	709 495 036	709 495 336	13.300
709 495 230	709 495 630	13.300	709 495 030	709 495 330	13.300
709 495 223	709 495 623	14.700	709 495 023	709 495 323	14.700
709 495 261	709 495 661	15.900	709 495 061	709 495 361	15.900
709 495 248	709 495 648	15.900	709 495 048	709 495 348	15.900
709 495 273	709 495 673	20.000	709 495 073	709 495 373	20.000
709 495 267	709 495 667	20.000	709 495 067	709 495 367	20.000

Min. (mm)	Max. (mm)	b (mm)	ID min. (mm)	e (mm)	M	f (mm)	h1 (mm)	h2 (mm)	PN Water (bar)	No. of bolt holes flange
386	408	191	84	3	M12	170	90	180	16	4
386	408	191	84	3	M12	170	90	180	16	8
404	430	241	90	3	M16	190	135	184	16	8
389	412	270	90	4	M16	170	135	184	16	4
389	412	270	90	4	M16	170	135	184	16	8
418	455	312	110	4	M16	180	160	184	16	4
418	455	312	110	4	M16	180	160	184	16	8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Data sheet

valid from: 6/20/25



Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>